

U.S. DEPARTMENT OF HOMELAND SECURITY FEDERAL EMERGENCY MANAGEMENT AGENCY National Flood Insurance Program

ELEVATION CERTIFICATE

Important: Read the instructions on pages 1-9.

OMB No. 1660-0008

Expiration Date: July 31, 2015

SECTION A – PROPERTY INFORMATION			INSURANCE COMPANY USE			
A1. Building Owner's Name The Kassekert's			/Number:			
A2. Building Street Address (including Apt., Unit, Suite, and/or 21 S. Yarmouth Ave.	Bldg. No.) or P.O. Route and Box N	o. Comp	any NAIC Number:			
City BOROUGH OF LONGPORT	State NJ ZIP Code 0	8403	the of the control of a 1 to 1			
A3. Property Description (Lot and Block Numbers, Tax Parcel BLOCK 82 LOT 5	Number, Legal Description, etc.)					
A4. Building Use (e.g., Residential, Non-Residential, Addition, Accessory, etc.) RESIDENTIAL A5. Latitude/Longitude: Lat. N 39.3176 Long. W 074.5204 Horizontal Datum: NAD 1927 NAD 1983 A6. Attach at least 2 photographs of the building if the Certificate is being used to obtain flood insurance. A7. Building Diagram Number 7 A8. For a building with a crawlspace or enclosure(s): a) Square footage of crawlspace or enclosure(s) b) Number of permanent flood openings in the crawlspace or enclosure(s) within 1.0 foot above adjacent grade 5 c) Total net area of flood openings? Nes No A9. For a building with an attached garage: a) Square footage of attached garage N/A sq ft b) Number of permanent flood openings in the attached garage within 1.0 foot above adjacent grade N/A c) Total net area of flood openings? Nes No						
SECTION B – FLOOD INSURANCE RATE MAP (FIRM) INFORMATION						
B1. NFIP Community Name & Community Number BOROUGH OF LONGPORT 345302	B2. County Name ATLANTIC COUNTY	B3. Si	ate			
B4. Map/Panel Number B5. Suffix B6. FIRM Index 345302/ 0001 B No Index Print	Effective/Revised Date	B8. Flood B9 Zone(s) A8**	Base Flood Elevation(s) (Zone AO, use base flood depth)			
☐ FIS Profile ☐ FIRM ☐ Community Determined ☐ Other/Source: ☐						
Indicate elevation datum used for the elevations in items a) Datum used for building elevations must be the same as the	through h) below. ⊠ NGVD 1929 □ at used for the BFE.		ource:easurement used.			
 a) Top of bottom floor (including basement, crawlspace, or et) b) Top of the next higher floor c) Bottom of the lowest horizontal structural member (V Zond) Attached garage (top of slab) e) Lowest elevation of machinery or equipment servicing the (Describe type of equipment and location in Comments) f) Lowest adjacent (finished) grade next to building (LAG) g) Highest adjacent (finished) grade next to building (HAG) h) Lowest adjacent grade at lowest elevation of deck or stain 	13.4 N/A. N/A. building 11.7 7.4 7.7	_	t			
SECTION D - SURVEYOR, ENGINEER, OR ARCHITECT CERTIFICATION						
This certification is to be signed and sealed by a land surveyor, information. I certify that the information on this Certificate repret I understand that any false statement may be punishable by find Check here if comments are provided on back of form. Check here if attachments. Certifier's Name Paul M. Koelling, PLS, CFM Title Licensed Land Surveyor Company Name Address 2161 Shore Road City Linwood	esents my best efforts to interpret the e or imprisonment under 18 U.S. Coo Were latitude and longitude in Sec licensed land surveyor? License Number N Paul H. Koelling & Associates, LLC-	data available. de, Section 1001. tion A provided by a es No	PLACE SEAL HERE			
Signature Date 7/29/15	Telephone (609)					

	and/or Bldg. No.) or P.O. Route a	om Section A. and Box No.	Policy Number:
21 S. Yarmouth Ave. City BOROUGH OF LONGPORT	State NJ	ZIP Code 08403	Company NAIC Number:
SECTION D - SURVI	EYOR, ENGINEER, OR ARC	HITECT CERTIFIC	ATION (CONTINUED)
Copy both sides of this Elevation Certificate for (1)			
comments		agonio company, ana (- · · ·
A8b.) Smart Vents Model #1540-510 engineered f *B8 & B9.) FEMA Pre-FIRM Zone "AE"Base F **C2a.) crawlspace enclosure ***C2e.) exterior air unit elev. is 18.2, ductwork el	Flood Elevation 10 ft. (NAVD88) c	each onverted = 11.3 ft. (N	GVD29)
ignature / All Company	Dat	te 7/29/15	
SECTION E - BUILDING ELEVATION IN	FORMATION (SURVEY NOT	REQUIRED) FOR	ZONE AO AND ZONE A (WITHOUT BFE)
For Zones AO and A (without BFE), complete Items and C. For Items E1–E4, use natural grade, if available. E1. Provide elevation information for the following grade (HAG) and the lowest adjacent grade (I a) Top of bottom floor (including basement, or b) Top of bottom floor (including basement, or E2. For Building Diagrams 6–9 with permanent flow (elevation C2.b in the diagrams) of the buildin E3. Attached garage (top of slab) is	able. Check the measurement use and check the appropriate boxes LAG). rawlspace, or enclosure) is rawlspace, or enclosure) is bod openings provided in Section g is feet feet meters about servicing the building is ailable, is the top of the bottom flo	ed. In Puerto Rico onles to show whether the	or, enter meters. elevation is above or below the highest adjacent meters □ above or □ below the HAG. meters □ above or □ below the LAG. ele pages 8–9 of Instructions), the next higher flood below the HAG. HAG. eters □ above or □ below the HAG. ance with the community's floodplain management
he property owner or owner's authorized represent	ERTY OWNER (OR OWNER'S		
Zone AO must sign here. The statements in Secti	ions A, B, and E are correct to the		
roperty Owner's or Owner's Authorized Represent			
ddress	City		State ZIP Code
	-		Telephone
ignature	Date		
	Date		☐ Check here if attachme
Comments	TION G - COMMUNITY INFO		NAL)
SECT e local official who is authorized by law or ordinance this Elevation Certificate. Complete the applicable ite . The information in Section C was taken from is authorized by law to certify elevation information. A community official completed Section E form	TION G – COMMUNITY INFO to administer the community's floc em(s) and sign below. Check the m n other documentation that has b mation. (Indicate the source and or a building located in Zone A (w	dplain management on the description of the description of the elevation of the description of the descripti	val.) rdinance can complete Sections A, B, C (or E), and ems G8–G10. In Puerto Rico only, enter meters. If by a licensed surveyor, engineer, or architect we data in the Comments area below.) or community-issued BFE) or Zone AO.
se local official who is authorized by law or ordinance this Elevation Certificate. Complete the applicable ite. The information in Section C was taken from is authorized by law to certify elevation information. A community official completed Section E formation. The following information (Items G4–G10) is	TION G – COMMUNITY INFO to administer the community's floc em(s) and sign below. Check the m n other documentation that has b mation. (Indicate the source and or a building located in Zone A (w	dplain management o leasurement used in It een signed and seale I date of the elevation ithout a FEMA-issued ain management purp	val.) rdinance can complete Sections A, B, C (or E), and ems G8–G10. In Puerto Rico only, enter meters. If by a licensed surveyor, engineer, or architect we data in the Comments area below.) or community-issued BFE) or Zone AO.
BEC1 e local official who is authorized by law or ordinance this Elevation Certificate. Complete the applicable ite . The information in Section C was taken from is authorized by law to certify elevation information. A community official completed Section E formula in the following information (Items G4–G10) is 14. Permit Number G5. Date Formula in the permit has been issued for: Relevation of as-built lowest floor (including baser in the BEE or (in Zone AO) depth of flooding at the builting in the permit in the	to administer the community's flocem(s) and sign below. Check the monother documentation that has be mation. (Indicate the source and or a building located in Zone A (was provided for community floodplatement) and the community floodplatement of the building:	dplain management of the deasurement used in it deen signed and sealed date of the elevation it date of the elevation if date of the elevation it date of the elevation in the elevation is determined by the elevation in the elevation in the elevation is determined by the elevation in the elevation is determined by the elevation in the elevation in the elevation is determined by the elevation in the elevation in the elevation is determined by the elevation in the elevation in the elevation is determined by the elevation in the eleva	val.) Indinance can complete Sections A, B, C (or E), and the sems G8–G10. In Puerto Rico only, enter meters. If by a licensed surveyor, engineer, or architect we data in the Comments area below.) or community-issued BFE) or Zone AO. Dises.
SECT e local official who is authorized by law or ordinance his Elevation Certificate. Complete the applicable ite The information in Section C was taken fror is authorized by law to certify elevation information. A community official completed Section E form the following information (Items G4–G10) is generally as the following information (Items G5. Date Figure 1). This permit has been issued for: New Control of the following bases are the following bases are the following information (Including bases). Community's design flood elevation:	to administer the community's flocem(s) and sign below. Check the monother documentation that has bornation. (Indicate the source and or a building located in Zone A (was provided for community floodplatement) and the building: Description Substantial in the source and some service of the building: Substantial in the building: Substantial in the source and some service and s	dplain management of the deasurement used in it deen signed and sealed date of the elevation it date of the elevation if date of the elevation it date of the elevation in the elevation is determined by the elevation in the elevation in the elevation is determined by the elevation in the elevation is determined by the elevation in the elevation in the elevation is determined by the elevation in the elevation in the elevation is determined by the elevation in the elevation in the elevation is determined by the elevation in the eleva	rdinance can complete Sections A, B, C (or E), and the sems G8–G10. In Puerto Rico only, enter meters. It by a licensed surveyor, engineer, or architect with data in the Comments area below.) or community-issued BFE) or Zone AO. Deses. The compliance of
SEC1 e local official who is authorized by law or ordinance his Elevation Certificate. Complete the applicable ite The information in Section C was taken fror is authorized by law to certify elevation information. A community official completed Section E form the following information (Items G4–G10) is described. The following information (Items G5. Date Formation of as-built lowest floor (including baser BFE or (in Zone AO) depth of flooding at the built community's design flood elevation:	to administer the community's flocem(s) and sign below. Check the ment of the documentation that has be mation. (Indicate the source and or a building located in Zone A (we so provided for community floodplate on the community	dplain management of leasurement used in little een signed and sealed date of the elevation ithout a FEMA-issued ain management purposed G6. Date Certification feet	rdinance can complete Sections A, B, C (or E), and the sems G8–G10. In Puerto Rico only, enter meters. It by a licensed surveyor, engineer, or architect with data in the Comments area below.) or community-issued BFE) or Zone AO. Deses. The compliance of
BEC1 e local official who is authorized by law or ordinance this Elevation Certificate. Complete the applicable ite. The information in Section C was taken from is authorized by law to certify elevation information. A community official completed Section E form the following information (Items G4–G10) is defended by the following information (Items G5. Date Fig. 1). This permit has been issued for: Because of the following at the build community design flood elevation: Community Section 1.	TION G – COMMUNITY INFO to administer the community's flocem(s) and sign below. Check the ment of the documentation that has be mation. (Indicate the source and or a building located in Zone A (we see provided for community floodplate of the community floodplate of the community floodplate of the building: Community Community floodplate of the building: Com	dplain management of the deasurement used in little een signed and sealed date of the elevation it	rdinance can complete Sections A, B, C (or E), and the sems G8–G10. In Puerto Rico only, enter meters. It by a licensed surveyor, engineer, or architect with data in the Comments area below.) or community-issued BFE) or Zone AO. Deses. The compliance of
e local official who is authorized by law or ordinance this Elevation Certificate. Complete the applicable ite . The information in Section C was taken fror is authorized by law to certify elevation information. A community official completed Section E formation. The following information (Items G4–G10) is defended. Permit Number G5. Date Formation is permit has been issued for:	TION G – COMMUNITY INFO to administer the community's flocem(s) and sign below. Check the ment of the documentation that has be mation. (Indicate the source and or a building located in Zone A (we see provided for community floodplate of the community floodplate of the community floodplate of the building: Community Community floodplate of the building: Com	right and the second se	rdinance can complete Sections A, B, C (or E), and the sems G8–G10. In Puerto Rico only, enter meters. It by a licensed surveyor, engineer, or architect with data in the Comments area below.) or community-issued BFE) or Zone AO. Deses. The compliance of

Building Photographs

Continuation Page			For Insurance Company Use:
Building Street Address (includ 21 S. Yarmouth Ave.	Policy Number		
City Lorngport	State NJ	ZIP Code 08403	Company NAIC Number

If su bmitting more photographs than will fit on the preceding page, affix the additional photographs below. Identify all phot⊚graphs with: date taken; "Front View" and "Rear View"; and, if required, "Right Side View" and "Left Side View."





Front View - Date of Photograph: (See Photo Stamp)

Rear View - Date of Photograph: (See Photo Stamp)





Right Side View - Date of Photograph: (See Photo Stamp)

Vent View - Date of Photograph: (See Photo Stamp)



ICC-ES Evaluation Report

ESR-2074

Reissued February 1, 2009

This report is subject to re-examination in two years.

www.icc-es.org | (800) 423-6587 | (562) 699-0543

A Subsidiary of the International Code Council®

DIVISION: 10—SPECIALTIES Section: 10230—Vents

REPORT HOLDER:

SMART VENT⁹, INC. 450 ANDBRO DRIVE, SUITE 2B PITMAN, NEW JERSEY 08071 (656) 307-1468 www.smartvent.com eval@smartvent.com

EVALUATION SUBJECT:

SMART VENT® AUTOMATIC FOUNDATION FLOOD VENTS: FLOODVENT™ MODEL #1540-520; FLOODVENT™ STACKING MODEL #1540-521; SMARTVENT™ MODEL #1540-510; SMARTVENT™ STACKING MODEL #1540-511; WOOD WALL FLOOD MODEL #1540-570; WOOD WALL FLOOD OVERHEAD DOOR MODEL #1540-574; FLOODVENT™ OVERHEAD DOOR MODEL #1540-524; SMARTVENT™ OVERHEAD DOOR MODEL #1540-514

1.0. EVALUATION SCOPE

Compliance with the following codes:

- 2006 International Building Code® (IBC)
- 2006 International Residential Code[®] (IRC)

Properties evaluated:

- Physical operation
- Water flow

2.0 USES

The Smart Vent[®] units are automatic foundation flood vents (AFFVs) employed to equalize hydrostatic pressure on nonfire-resistance-rated foundation walls, rolling-type overhead doors and building walls subject to rising or falling flood waters. Certain models also allow natural ventilation in accordance with Section 1203 of the IBC or Section 408.1 of the IRC.

3.0 DESCRIPTION

3.1 General:

When subjected to pressure from rising water, the Smart Vent® AFFVs disengage, then pivot open to allow flow in either direction to equalize water level and hydrostatic pressure from one side of the foundation to the other. The AFFV pivoting door is normally held in the closed position by a buoyant release device. When subjected to rising water, the buoyant release device causes the unit to

unlatch, allowing the plate to rotate out of the way and allow flow. The water level stabilizes, equalizing the lateral forces. Each unit is fabricated from stainless steel, and each opening provides 76 square inches (49 032 mm²) of net free area for flood mitigation in the open position. The SmartVENT™ Stacking Model #1540-511 and FloodVENT™ Stacking Model #1540-521 units each contain two vertically arranged openings per unit, providing 152 square inches (98 064 mm²) of net free area for flood mitigation in the open position.

3.2 Engineered Opening:

The AFFVs comply with the design principle noted in Section 2.6.2.2 of ASCE/SEI 24 for a maximum rate of rise and fall of 5.0 feet per hour (0.423 mm/s). In order to comply with the engineered opening requirement of ASCE/SEI 24, Smart Vent AFFVs must be installed in accordance with Section 4.0.

3.3 Model Sizes:

The FloodVENT™ Model #1540-520, SmartVENT™ Model #1540-510, FloodVENT™ Overhead Door Model #1540-524, and SmartVENT™ Overhead Door Model #1540-514 units measure 15³/₄ inches wide by 7³/₄ inches high (400 by 196.9 mm). The Wood Wall Flood Model #1540-570 and Wood Wall Flood Overhead Door Model #1540-574 units measure 14 inches wide by 8³/₄ inches high (355.6 by 222.25 mm). The SmartVENT™ Stacking Model #1540-511 and FloodVENT™ Stacking Model #1540-521 units measure 16 inches wide by 16 inches high (406.4 by 406.4 mm).

3.4 Ventilation:

The SmartVENT® Model #1540-510 and SmartVENT® Overhead Door Model #1540-514 both have screen covers with ¹/₄-inch-by-¹/₄-inch (6.35 by 6.35 mm) openings, yielding 51 square inches (32 903 mm²) of net free area to supply natural ventilation. The SmartVENT™ Stacking Model #1540-511 consists of two Model #1540-510 units in one assembly, and provides 102 square inches (65 806 mm²) of net free area to supply natural ventilation. Other AFFVs recognized in this report do not offer natural ventilation.

4.0 INSTALLATION

SmartVENT[®] and FloodVENT[™] are designed to be installed into walls or overhead doors of existing or new construction from the exterior side. Installation of the vents must be in accordance with the manufacturer's instructions, the applicable code and this report. The mounting straps allow mounting in wood, masonry and concrete walls up to 12 inches (305 mm) thick. In order to