U.S. DEPARTMENT OF HOMELAND SECURITY FEDERAL EMERGENCY MANAGEMENT AGENCY National Flood Insurance Program

ELEVATION CERTIFICATE

Important: Read the instructions on pages 1-9.

8412

OMB No. 1660-0008

Expiration Date: July 31, 2015

A1 Building Owner's No.								NST AND ENDOUGHE
A1 Duilding Owneds News TUE UPOOUS								Alliquis 1
A2. Building Street Address (including Apt., Unit, Suite, and/or Bldg. No.) or P.O. Route and Box No. #3217 VENTNOR AVENUE								NEW COLLEGE
City BOROUGH OF				State NJ	ZIP Code	08403	COLOR COLOR COLOR	
A3. Property Description (BLOCK 84 LOT 2	(Lot and Block Nu	ımbers, Tax Parcel	Numbe	r, Legal Descr	ption, etc.)			1 1 2015
A4. Building Use (e.g., Re A5. Latitude/Longitude: La A6. Attach at least 2 photo A7. Building Diagram Nun A8. For a building with a c a) Square footage of b) Number of perman	at. 39.3184 Longographs of the bunber 7 crawlspace or enderawlspace or endert flood opening	3. <u>-74.5210</u> Hilding if the Certifications of the Certifications of the Certifications of the Certification of th	orizonta ate is be <u>1110</u> e	Datum: 1	NAD 1927 🔯 tain flood insu A9. For a a) So b) Nu	irance. building with an at quare footage of at umber of permane	ttached ga	arage <u>N/A</u> sq ft penings in the attached garage
or enclosure(s) within 1.0 foot above adjacent grade c) Total net area of flood openings in A8.b d) Engineered flood openings? Yes No Total net area of flood openings? Yes No Total net area of flood openings? G) Total net area of flood openings? G) Engineered flood openings								t grade <u>N/A</u> gs in A9.b <u>N/A</u> sq in □ Yes ⊠ No
	SECT	TION B - FLOOD	INSU	RANCE RAT				
B1. NFIP Community Name BOROUGH OF LONGPOR	e & Community N T 345302	lumber		ounty Name NTIC COUNTY	,		B3. Sta	ate
B4. Map/Panel Number 345302/ 0001	B5. Suffix B	B6. FIRM Index I		B7. FIRM Effective/Re 08/15/	vised Date	B8. Flood Zone(s) A8**	B9.	Base Flood Elevation(s) (Zone AO, use base flood depth) 10**
FIS Profile B11. Indicate elevation datu B12. Is the building located Designation Date:	m used for BFE i in a Coastal Barr	☐ Community Det n Item B9: ☑ NG\ ier Resources Syste	VD 1929 em (<u>C</u> BI	N.RS) area or Ot	ther/Source: _ AVD 1988 herwise Prote ☐ OPA	Other/Source	:	☐ Yes
	SECTION	C - BUILDING	ELEVA	ATION INFO	RMATION (S	SURVEY REQU	IRED)	
C1. Building elevations are be *A new Elevation Certific	pased on:	☐ Construction Dr	rawinge*					
C2. Elevations – Zones A1–, below according to the benchmark Utilized: priv Indicate elevation datum	A30, AE, AH, A (voliding diagrams state) used for the elever	ed when construction with BFE), VE, V1- specified in Item A7 vations in items a) to	on of the V30, V (. In Pue Verti	e building is co with BFE), AR rto Rico only, e cal Datum: No h) below	, AR/A, AR/AB enter meters. GVD29	E, AR/A1–A30, AF	VAH, AR/	
C2. Elevations – Zones A1–, below according to the b Benchmark Utilized: priv Indicate elevation datum Datum used for building	A30, AE, AH, A (vollding diagram seate I used for the elevelevations must be	ed when construction with BFE), VE, V1— specified in Item A7 vations in items a) to the same as that	on of the V30, V (. In Pue Verti hrough I	e building is co with BFE), AR rto Rico only, a ical Datum: <u>No</u> h) below. \(\text{No} \) or the BFE.	mplete. , AR/A, AR/AI enter meters. GVD29	E, AR/A1–A30, AF	R/AH, AR/	AO. Complete Items C2.a-h
C2. Elevations – Zones A1– below according to the b Benchmark Utilized: priv Indicate elevation datum Datum used for building a) Top of bottom floor (in b) Top of the next higher c) Bottom of the lowest h d) Attached garage (top of e) Lowest elevation of m	A30, AE, AH, A (ouilding diagram state) used for the elevations must lucluding basement floor norizontal structurof slab) achinery or equip	ed when construction with BFE), VE, V1— specified in Item A7 vations in items a) to be the same as that at, crawlspace, or ear all member (V Zone) ment servicing the	on of the V30, V ('. In Pue Verti through I t used fo nclosure	e building is co (with BFE), AR rto Rico only, e ical Datum: No h) below. Mo or the BFE.	mplete. , AR/A, AR/Alenter meters. GVD29 GVD 1929 7.0** 15.8 N/A. N/A.	E, AR/A1–A30, AR I NAVD 1988 □ 0 Chec *	Other/Souck the mea feet feet feet feet feet	AO. Complete Items C2.a-h urce: asurement used. meters meters meters meters meters meters
C2. Elevations – Zones A1–, below according to the below according t	A30, AE, AH, A (ouilding diagram state) used for the elevations must be cluding basement floor norizontal structurof slab) achinery or equippment and locationed) grade next thed) grade next thed) grade next thed) grade next to suit the suit and suit the suit the suit and suit the suit and suit the suit and suit the suit and s	ed when construction with BFE), VE, V1— specified in Item A7 vations in items a) to be the same as that at, crawlspace, or ear all member (V Zone ament servicing the continuous comments) building (LAG) to building (HAG)	on of the V30, V (In Pue Verti through I t used fo nclosure es only) building	e building is co (with BFE), AR rto Rico only, e ical Datum: No h) below. Mo or the BFE.	mplete. , AR/A, AR/Alenter meters. GVD29 GVD 1929 7.0** 15.8 N/A. N/A. 13.2*	E, AR/A1–A30, AR I NAVD 1988 Chec *	Other/Souck the mea	AO. Complete Items C2.a-h urce: asurement used. meters meters meters meters
C2. Elevations – Zones A1–, below according to the below according to the benchmark Utilized: priv Indicate elevation datum Datum used for building a) Top of bottom floor (in b) Top of the next higher c) Bottom of the lowest higher c) Bottom of the lowest higher d) Attached garage (top of e) Lowest elevation of mice (Describe type of equif) Lowest adjacent (finish h) Lowest adjacent grade	A30, AE, AH, A (ouilding diagram state) used for the elevations must be cluding basement floor norizontal structurof slab) achinery or equippment and locationed) grade next to the diagrade next to eat lowest elevat	ed when construction with BFE), VE, V1— specified in Item A7 vations in items a) to be the same as that at, crawlspace, or element servicing the continuous comments) to building (LAG) to building (HAG) tion of deck or stairs	on of the V30, V (In Pue Verti hrough I t used fo nclosure es only) building	e building is co with BFE), AR rto Rico only, e ical Datum: No h) below. or the BFE. e floor) ing structural s	mplete. , AR/A, AR/Alenter meters. GVD29 GVD 1929 T.0** 15.8 N/A. N/A. 13.2* 6.8 7.3 upport ARCHITEC	E, AR/A1–A30, AR NAVD 1988 Chec *	Other/Sou	AO. Complete Items C2.a-h urce: asurement used.
C2. Elevations – Zones A1– below according to the b Benchmark Utilized: priv Indicate elevation datum Datum used for building a) Top of bottom floor (in b) Top of the next higher c) Bottom of the lowest h d) Attached garage (top e) Lowest elevation of m (Describe type of equi f) Lowest adjacent (finist g) Highest adjacent (finis	A30, AE, AH, A (ouilding diagram state) used for the elevations must be cluding basement floor norizontal structurof slab) achinery or equippement and locationed) grade next to the diagram of slab at lowest elevate statement may be stare provided on	ed when construction with BFE), VE, V1— specified in Item A7 vations in items a) to be the same as that it, crawlspace, or element servicing the continuous comments of building (LAG) to building (HAG) to buildi	on of the V30, V (In Pue Verti through I t used fo nclosure es only) building R, ENG engineer sents my or impri Were la	e building is co with BFE), AR rto Rico only, e ical Datum: No h) below. or the BFE. e floor) GINEER, OR r, or architect a r best efforts to sonment unde	mplete. , AR/A, AR/Alenter meters. GVD29 GVD 1929 GVD 1929 7.0** 15.8 N/A. N/A. 13.2* 6.8 7.3 upport N/A. ARCHITEC uthorized by Interpret the r 18 U.S. Cod gitude in Section	E, AR/A1–A30, AR NAVD 1988 Chec * Chec * T CERTIFICATI aw to certify eleva data available. le, Section 1001. ion A provided by	Other/Souther/	AO. Complete Items C2.a-h urce: asurement used. meters
C2. Elevations – Zones A1– below according to the below according to	A30, AE, AH, A (ouilding diagram state) used for the elevations must be clevations and location of slab) are clevationary or equipped per and location of slab (e. at lowest elevation of slab) are clevations of slab (e. at lowest elevation of slab) and sealed be clevation of slab (e. at lowest elevation of slab) and sealed be information on the slab clevation of slab (e. at lowest elevation of slab (ed when construction with BFE), VE, V1— specified in Item A7 vations in items a) to be the same as that it, crawlspace, or element servicing the continuous comments of building (LAG) to building (HAG) to buildi	on of the V30, V (In Pue Verti through I t used fo nclosure es only) building R, ENG engineer sents my or impri Were la	e building is co with BFE), AR rto Rico only, e ical Datum: No h) below. or the BFE. e floor) ing structural s ing structural s ing structural s continuous efforts to sonment unde atitude and lon d land surveyo	mplete. , AR/A, AR/Alenter meters. GVD29 GVD 1929 GVD 1929 GVD 1929 GVD 15.8 N/A. N/A. 13.2* 6.8 7.3 upport N/A. ARCHITEC uthorized by I of interpret the r 18 U.S. Cod gitude in Sectir? Ye	E, AR/A1–A30, AF NAVD 1988 Chec * Chec * T CERTIFICATI aw to certify eleva data available. ie, Section 1001. ion A provided by s No	Other/Souther/	AO. Complete Items C2.a-h urce: asurement used.
C2. Elevations – Zones A1– below according to the lowest higher conditions and the below according to the below ac	A30, AE, AH, A (ouilding diagram state) used for the elevations must be clevations achinery or equipal properties and location hed) grade next to be calculated by the clevation of the	ed when construction with BFE), VE, V1— specified in Item A7 vations in items a) to be the same as that the crawlspace, or enter a limit of the same as that the crawlspace, or enter a limit of the same as that the crawlspace, or enter a limit of the same as that the crawlspace, or enter a limit of the same as that the crawlspace, or enter a limit of the same as that the same as the same as that the same as that the same as that the same as the same as that the same as that the same as that the same as that the same as t	on of the V30, V (In Pue Verti through I t used fo nclosure es only) building R, ENG engineer sents my or impri Vere la licensed	e building is co with BFE), AR rto Rico only, e ical Datum: No h) below. or the BFE. e floor) ing structural s GINEER, OR r, or architect a y best efforts to somment unde atitude and lon d land surveyo Licen.	mplete. , AR/A, AR/Alenter meters. GVD29 GVD 1929 GVD 1929 7.0** 15.8 N/A. N/A. 13.2* 6.8 7.3 upport N/A. ARCHITEC uthorized by Interpret the r 18 U.S. Cod gitude in Section? Yese Number N	E, AR/A1–A30, AR NAVD 1988 Chec * T CERTIFICATI aw to certify eleva data available. e, Section 1001. ion A provided by	Other/Souther/	AO. Complete Items C2.a-h urce: asurement used. meters
C2. Elevations – Zones A1–, below according to the below according t	A30, AE, AH, A (soliding diagram state) used for the elevations must be elevations must be cluding basement floor norizontal structure of slab) achinery or equippment and locationed) grade next to the diagram of the elevations o	ed when construction with BFE), VE, V1— specified in Item A7 vations in items a) to be the same as that it, crawlspace, or element servicing the continuous comments of building (LAG) to building (HAG) to buildi	on of the V30, V (In Pue Verti through I t used fo nclosure es only) building R, ENG engineer sents my or impri Vere la licensed	e building is co with BFE), AR rto Rico only, e ical Datum: No h) below. or the BFE. e floor) ing structural s GINEER, OR r, or architect a y best efforts to somment unde atitude and lon d land surveyo Licen.	mplete. , AR/A, AR/Alenter meters. GVD29 GVD 1929 T.0** 15.8 N/A. N/A. 13.2* 6.8 7.3 upport ARCHITEC uthorized by Interpret the results of the r	E, AR/A1–A30, AF NAVD 1988 Chec * Chec * T CERTIFICATI aw to certify eleva data available. ie, Section 1001. ion A provided by s No	Other/Souther/	AO. Complete Items C2.a-h urce: asurement used.
C2. Elevations – Zones A1– below according to the below according to	A30, AE, AH, A (ouilding diagram state) used for the elevations must be clevations and location of slab) are clevations of slab (or clevation) grade next to clevate at lowest elevation of slab (or clevation) grade next to clevation of slab (or clevation) grad	ed when construction with BFE), VE, V1— specified in Item A7 vations in items a) to be the same as that the crawlspace, or element servicing the continuous comments of building (LAG) to building (HAG) to building (HAG).	on of the V30, V (In Pue Verti through I t used fo nclosure es only) building R, ENG engineer sents my or impri Vere la licensed	e building is co with BFE), AR rto Rico only, e cal Datum: No h) below. or the BFE. e floor) ing structural s colorial services and services and services ing structural s colorial services ing structural s ing structural s colorial services ing structural s colorial services ing structural s ing structural s colorial services ing structural s colorial services ing structural s in	mplete. , AR/A, AR/Alenter meters. GVD29 GVD 1929 T.0** 15.8 N/A. N/A. 13.2* 6.8 7.3 upport ARCHITEC uthorized by Interpret the results of the r	T CERTIFICATI aw to certify eleva data available. e, Section 1001. ion A provided by S No J24GS 04328800	Other/Souther/	AO. Complete Items C2.a-h urce: asurement used.

LL VALION OLIVIII IOAIL, Page & IMPORTANT: In these spaces, copy the corresponding information from Section A. ZOGONSURANOG OGMEANYGGE Building Street Address (including Apt., Unit, Suite, and/or Bldg. No.) or P.O. Route and Box No. #3217 VENTNOR AVENUE City BOROUGH OF LONGPORT State NJ ZIP Code 08403 Pempany NAIG Number SECTION D - SURVEYOR, ENGINEER, OR ARCHITECT CERTIFICATION (CONTINUED) Copy both sides of this Elevation Certificate for (1) community official, (2) insurance agent/company, and (3) building owner. Comments *A8b.) SEE ATTACHED letter from Architect **B8 & B9.) FEMA Pre-FIRM Zone "AE".....Base Flood Elevation 9 ft. (NAVD88) converted = 10.3 ft. (NGVD29) **C2a.) enclosure ****C2e.) furnace (elev 13.2).....ductwork (elev 13.9).....exterior air unit (elev 15.5) Signature SECTION E - BUILDING ELEVATION INFORMATION (SURVEY NOT REQUIRED) FOR ZONE AO AND ZONE A (WITHOUT BFE) For Zones AO and A (without BFE), complete Items E1-E5. If the Certificate is intended to support a LOMA or LOMR-F request, complete Sections A, B, and C. For Items E1-E4, use natural grade, if available. Check the measurement used. In Puerto Rico only, enter meters. E1. Provide elevation information for the following and check the appropriate boxes to show whether the elevation is above or below the highest adjacent grade (HAG) and the lowest adjacent grade (LAG). a) Top of bottom floor (including basement, crawlspace, or enclosure) is ☐ feet ☐ meters ☐ above or ☐ below the HAG. b) Top of bottom floor (including basement, crawlspace, or enclosure) is ☐ feet ☐ meters ☐ above or ☐ below the LAG. For Building Diagrams 6-9 with permanent flood openings provided in Section A Items 8 and/or 9 (see pages 8-9 of Instructions), the next higher floor (elevation C2.b in the diagrams) of the building is ☐ feet ☐ meters ☐ above or ☐ below the HAG. E3. Attached garage (top of slab) is ☐ feet ☐ meters ☐ above or ☐ below the HAG. E4. Top of platform of machinery and/or equipment servicing the building is _____ ☐ feet ☐ meters ☐ above or ☐ below the HAG. Zone AO only: If no flood depth number is available, is the top of the bottom floor elevated in accordance with the community's floodplain management SECTION F - PROPERTY OWNER (OR OWNER'S REPRESENTATIVE) CERTIFICATION The property owner or owner's authorized representative who completes Sections A, B, and E for Zone A (without a FEMA-issued or community-issued BFE) or Zone AO must sign here. The statements in Sections A, B, and E are correct to the best of my knowledge. Property Owner's or Owner's Authorized Representative's Name Address City State ZIP Code Signature Date Telephone Comments Check here if attachments. SECTION G - COMMUNITY INFORMATION (OPTIONAL) The local official who is authorized by law or ordinance to administer the community's floodplain management ordinance can complete Sections A, B, C (or E), and G of this Elevation Certificate. Complete the applicable item(s) and sign below. Check the measurement used in Items G8-G10. In Puerto Rico only, enter meters. The information in Section C was taken from other documentation that has been signed and sealed by a licensed surveyor, engineer, or architect who is authorized by law to certify elevation information. (Indicate the source and date of the elevation data in the Comments area below.) G2. 🗌 A community official completed Section E for a building located in Zone A (without a FEMA-issued or community-issued BFE) or Zone AO. G3. □ The following information (Items G4-G10) is provided for community floodplain management purposes. G4. Permit Number G5. Date Permit Issued G6. Date Certificate Of Compliance/Occupancy Issued G7. This permit has been issued for: ☐ New Construction ☐ Substantial Improvement G8. Elevation of as-built lowest floor (including basement) of the building: ☐ feet ☐ meters Datum G9. BFE or (in Zone AO) depth of flooding at the building site: ☐ feet ☐ meters Datum _ G10. Community's design flood elevation: ☐ meters ☐ feet Datum Local Official's Name Title Community Name Telephone Signature Date Comments Check here if attachments.

MARK A. ZAWACKI A.I.A

1555 Zion Road Suite 204 Northfield, N.J. 08225 Phone 609-709-3292 Fax 609-484-9040

May 8, 2015

Paul H. Koelling PLS 2161 Shore Road Linwood, N.J. 08221

Re: Amy and Joe Hirsch Residence 3217 Ventnor Ave Longport, N.J. 08402

Attention: Steve

This letter is to certify flood openings for the above referenced project.

Mark A. Zawacki A.I.A. Lic # 21AI01338380

SINCERELY,

Building Photographs

	Continuation F	For Insurance Company Use:	
Building Street Address (includ 3217 Ventnor Blvd.	Policy Number		
City Longport	State NJ	ZIP Code 08403	Company NAIC Number

If submitting more photographs than will fit on the preceding page, affix the additional photographs below. Identify all photographs with: date taken; "Front View" and "Rear View"; and, if required, "Right Side View" and "Left Side View."





Front View - Date of Photograph: (See Photo Stamp)

Rear View - Date of Photograph: (See Photo Stamp)





Vent View - Date of Photograph: (See Photo Stamp)

Left Side View - Date of Photograph: (See Photo Stamp)



ICC-ES Evaluation Report

ESR-2074

Reissued February 1, 2009

This report is subject to re-examination in two years.

www.icc-es.org | (800) 423-6587 | (562) 699-0543

A Subsidiary of the International Code Council®

DIVISION: 10—SPECIALTIES Section: 10230—Vents

REPORT HOLDER:

SMART VENT[®], INC. 450 ANDBRO DRIVE, SUITE 2B PITMAN, NEW JERSEY 08071 (856) 307-1468 www.smartvent.com eval@smartvent.com

EVALUATION SUBJECT:

SMART VENT® AUTOMATIC FOUNDATION FLOOD VENTS: FLOODVENT™ MODEL #1540-520; FLOODVENT™ STACKING MODEL #1540-521; SMARTVENT™ MODEL #1540-510; SMARTVENT™ STACKING MODEL #1540-511; WOOD WALL FLOOD MODEL #1540-570; WOOD WALL FLOOD OVERHEAD DOOR MODEL #1540-574; FLOODVENT™ OVERHEAD DOOR MODEL #1540-524; SMARTVENT™ OVERHEAD DOOR MODEL #1540-514

1.0 EVALUATION SCOPE

Compliance with the following codes:

- 2006 International Building Code® (IBC)
- 2006 International Residential Code® (IRC)

Properties evaluated:

- Physical operation
- Water flow

2.0 USES

The Smart Vent[®] units are automatic foundation flood vents (AFFVs) employed to equalize hydrostatic pressure on nonfire-resistance-rated foundation walls, rolling-type overhead doors and building walls subject to rising or falling flood waters. Certain models also allow natural ventilation in accordance with Section 1203 of the IBC or Section 408.1 of the IRC.

3.0 DESCRIPTION

3.1 General:

When subjected to pressure from rising water, the Smart Vent® AFFVs disengage, then pivot open to allow flow in either direction to equalize water level and hydrostatic pressure from one side of the foundation to the other. The AFFV pivoting door is normally held in the closed position by a buoyant release device. When subjected to rising water, the buoyant release device causes the unit to

unlatch, allowing the plate to rotate out of the way and allow flow. The water level stabilizes, equalizing the lateral forces. Each unit is fabricated from stainless steel, and each opening provides 76 square inches (49 032 mm²) of net free area for flood mitigation in the open position. The SmartVENT™ Stacking Model #1540-511 and FloodVENT™ Stacking Model #1540-521 units each contain two vertically arranged openings per unit, providing 152 square inches (98 064 mm²) of net free area for flood mitigation in the open position.

3.2 Engineered Opening:

The AFFVs comply with the design principle noted in Section 2.6.2.2 of ASCE/SEI 24 for a maximum rate of rise and fall of 5.0 feet per hour (0.423 mm/s). In order to comply with the engineered opening requirement of ASCE/SEI 24, Smart Vent AFFVs must be installed in accordance with Section 4.0.

3.3 Model Sizes:

The FloodVENT™ Model #1540-520, SmartVENT™ Model #1540-510, FloodVENT™ Overhead Door Model #1540-524, and SmartVENT™ Overhead Door Model #1540-514 units measure 15³/₄ inches wide by 7³/₄ inches high (400 by 196.9 mm). The Wood Wall Flood Model #1540-570 and Wood Wall Flood Overhead Door Model #1540-574 units measure 14 inches wide by 8³/₄ inches high (355.6 by 222.25 mm). The SmartVENT™ Stacking Model #1540-511 and FloodVENT™ Stacking Model #1540-521 units measure 16 inches wide by 16 inches high (406.4 by 406.4 mm).

3.4 Ventilation:

The SmartVENT® Model #1540-510 and SmartVENT® Overhead Door Model #1540-514 both have screen covers with ¹/₄-inch-by-¹/₄-inch (6.35 by 6.35 mm) openings, yielding 51 square inches (32 903 mm²) of net free area to supply natural ventilation. The SmartVENT™ Stacking Model #1540-511 consists of two Model #1540-510 units in one assembly, and provides 102 square inches (65 806 mm²) of net free area to supply natural ventilation. Other AFFVs recognized in this report do not offer natural ventilation.

4.0 INSTALLATION

SmartVENT[®] and FloodVENT[™] are designed to be installed into walls or overhead doors of existing or new construction from the exterior side. Installation of the vents must be in accordance with the manufacturer's instructions, the applicable code and this report. The mounting straps allow mounting in wood, masonry and concrete walls up to 12 inches (305 mm) thick. In order to

