

B-8 L-15.01

1406 Atlantic Ave.  
Topkis

8/15.01

O.M.B. No 3067-0077  
Expires May 31, 1993

# ELEVATION CERTIFICATE

**FEDERAL EMERGENCY MANAGEMENT AGENCY**  
**NATIONAL FLOOD INSURANCE PROGRAM**

**ATTENTION:** Use of this certificate does not provide a waiver of the flood insurance purchase requirement. This form is used only to provide elevation information necessary to ensure compliance with applicable community floodplain management ordinances, to determine the proper insurance premium rate, and/or to support a request for a Letter of Map Amendment or Revision (LOMA or LOMR). Instructions for completing this form can be found on the following pages.

SECTION A PROPERTY INFORMATION		FOR INSURANCE COMPANY USE
BUILDING OWNER'S NAME <b>STUART AND ZELDA TOPKIS</b>		POLICY NUMBER
STREET ADDRESS (Including Apt., Unit, Suite and/or Bldg. Number) OR P.O. ROUTE AND BOX NUMBER <b>FIFTEENTH &amp; ATLANTIC AVENUES</b>		COMPANY NAIC NUMBER

OTHER DESCRIPTION (Lot and Block Numbers, etc.)  
**BLOCK 8, LOT 15.01**

CITY **LONGPORT** STATE **NEW JERSEY** ZIP CODE **08402**

## SECTION B FLOOD INSURANCE RATE MAP (FIRM) INFORMATION

Provide the following from the proper FIRM (See Instructions):

1. COMMUNITY NUMBER	2. PANEL NUMBER	3. SUFFIX	4. DATE OF FIRM INDEX	5. FIRM ZONE	6. BASE FLOOD ELEVATION (in AO Zones, use depth)
345302	0001	B	8/15/83	A-8	10.00'

7. Indicate the elevation datum system used on the FIRM for Base Flood Elevations (BFE):  NGVD '29  Other (describe on back)  
 8. For Zones A or V, where no BFE is provided on the FIRM, and the community has established a BFE for this building site, indicate the community's BFE: 12.5 feet NGVD (or other FIRM datum—see Section B, Item 7).

## SECTION C BUILDING ELEVATION INFORMATION

1. Using the Elevation Certificate Instructions, indicate the diagram number from the diagrams found on Pages 5 and 6 that best describes the subject building's reference level 5.
- 2(a). FIRM Zones A1-A30, AE, AH, and A (with BFE). The top of the reference level floor from the selected diagram is at an elevation of 12.5 feet NGVD (or other FIRM datum—see Section B, Item 7).
- (b). FIRM Zones V1-V30, VE, and V (with BFE). The bottom of the lowest horizontal structural member of the reference level from the selected diagram, is at an elevation of 12.5 feet NGVD (or other FIRM datum—see Section B, Item 7).
- (c). FIRM Zone A (without BFE). The floor used as the reference level from the selected diagram is 12.5 feet above  or below  (check one) the highest grade adjacent to the building.
- (d). FIRM Zone AO. The floor used as the reference level from the selected diagram is 12.5 feet above  or below  (check one) the highest grade adjacent to the building. If no flood depth number is available, is the building's lowest floor (reference level) elevated in accordance with the community's floodplain management ordinance?  Yes  No  Unknown
3. Indicate the elevation datum system used in determining the above reference level elevations:  NGVD '29  Other (describe under Comments on Page 2). (NOTE: If the elevation datum used in measuring the elevations is different than that used on the FIRM [see Section B, Item 7], then convert the elevations to the datum system used on the FIRM and show the conversion equation under Comments on Page 2.)
4. Elevation reference mark used appears on FIRM:  Yes  No (See Instructions on Page 4)
5. The reference level elevation is based on:  actual construction  construction drawings  
(NOTE: Use of construction drawings is only valid if the building does not yet have the reference level floor in place, in which case this certificate will only be valid for the building during the course of construction. A post-construction Elevation Certificate will be required once construction is complete.)
6. The elevation of the lowest grade immediately adjacent to the building is: 5.8 feet NGVD (or other FIRM datum—see Section B, Item 7).


## SECTION D COMMUNITY INFORMATION

1. If the community official responsible for verifying building elevations specifies that the reference level indicated in Section C, Item 1 is not the "lowest floor" as defined in the community's floodplain management ordinance, the elevation of the building's "lowest floor" as defined by the ordinance is: 12.5 feet NGVD (or other FIRM datum—see Section B, Item 7).
2. Date of the start of construction or substantial improvement \_\_\_\_\_

The diagrams above illustrate the points at which the elevations should be measured in A Zones and V Zones.

Elevations for all A Zones should be measured at the top of the lowest horizontal structural member.

Elevations for all V Zones should be measured at the bottom of the reference level floor.



FINISH FLOOR ELEVATION = 12.55'

GRADE ELEVATION = 5.89'

COMMENTS:

Copies should be made of this Certificate for: 1) Community official, 2) Insurance agent/company, and 3) building owner.

SIGNATURE DATE 3/25/92 PHONE 344-8194

400 N. DOVER AVENUE  
ATLANTIC CITY NEW JERSEY 08401  
CITY STATE ZIP  
ARTHUR W. PONZIO CO. & ASSO., INC.  
TITLE COMPANY NAME  
9343  
LICENCE NUMBER (or Affix Seal)  
ARTHUR W. PONZIO SR.  
LAND SURVEYOR

I certify that the information in Sections B and C on this certificate represents my best efforts to interpret the data available.

Reference level diagrams 6, 7 and 8 - Designating Featuress - If the certifier is unable to certify to breakaway/non-breakaway wall, enclosure size, location of servicing equipment, area use, wall openings, or unfinished area Feature(s), then list the Feature(s) not included in the certificate.

Owner's representative may also sign the certificate. In the case of Zones AD and A (without a FEMA or community management plan issued BFE), a building official, a property owner, or an certifier, in the case of Zones AE, AH, (With BFE), V1-V30, VE, and V (with BFE) is required.

This certification is to be signed by a land surveyor, engineer, or architect who is authorized by state or local law to certify elevation information when the elevation information for Zones A1-A30, AE, AH, (With BFE), V1-V30, VE, and V (with BFE) is required.